

# Filter Housing - Standard Diameter

The Blue Standard Diameter Filter Housing is manufactured from Polypropylene which has excellent chemical resistance enabling it to be used in a variety of applications within the Domestic, Rural, Commercial and Light Industrial fields. The Filter Housing has a Double O-Ring Seal built into the Housing Bowl providing it with added protection against leakage.

The Housing Cap has a Pressure Relief Button built in and mounting bosses to accommodate a Wall Mounting Bracket for easy installation. Unlike clear housings the Blue Polypropylene is opaque preventing light from penetrating which causes microbiological growth inside the filter housing.

## Typical Applications

- Point of Use (POU)
- Whole of House (20" Housing)
- Rural
- Ice Machines
- Beverage Dispensers
- Recreation Vehicles
- Marine
- Domestic
- Commercial
- Light Industrial

## General Specifications

- Port Size : 3/4" BSP
- Dimensions **10"** **20"**  
Width: 130mm (5.1") 130mm (5.1")  
Height: 335mm (13.2") 580mm (22.8")
- Temperature Ranges: 4.4°C - 43°C  
(40°F - 110°F)
- Operating Pressure: 690 kPa (100 psi)  
(Maximum)
- Recommended Flow Rate: **10"** 38 Lpm  
(Maximum) **20"** 76 Lpm

**NOTE:** Flow rate will vary depending on type of filter cartridge installed.  
(Filter Cartridge NOT included)

## Optional Extras

- A. Wrench P/No. WAW1020HS
- B. Mounting Bracket P/No. WABS1020SW  
Double Bracket also available.



**Warning:**  
For drinking water applications, do not use water that is microbiologically unsafe or of unknown quality without adequate disinfection.

Series: WHSB34



Model No.

10"

WH10SB34DO

Kits (w/bracket & wrench)

WH10SB34DOK

20"

WH20SB34DO

WH20SB34DOK

**Watermart**  
Water...cleaned fresh daily

3/4" Blue D.O.  
Filter Housing