

EMPTY CARTRIDGE CANISTERS

FEATURES AND BENEFITS

- Price Competitive
- Simple Installation
- Refillable
- Standard Cartridge Sizes
- Wide Variety of Applications
- Individually Wrapped and Sealed

TYPICAL APPLICATIONS

(Depending on Media used)

- Post-Reverse Osmosis (RO)
- Battery Water
- Scale Prevention
- pH Correction
- D.I. (Deionization)

The Canisters are designed to meet the market requirements for refillable cartridges which can be loaded with various Medias. The Polypropylene construction in combination with different medias make them suitable for a wide range of applications including: pH correction, Chlorine reduction, Hardness removal, Organic Colour and Taste correction, and Deionization.

The Up Flow design of the cartridge ensures maximum contact time with the media for optimum performance and incorporates a compression pad to discourage channeling. The Canister has a Pre-Filter pad for Sediment removal and a 10 micron Post-Filter to prevent media fines from passing. The base of the canister is threaded for quick and easy media replacement.



GENERAL SPECIFICATIONS

Standard Diameter:

Available Lengths	250mm (9 ⁷ / ₈ " 508mm (20")
Outside Diameter	73mm (2 ⁷ / ₈ "
Inside Diameter	25mm (1")
Canister Capacity	(250mm) 0.8 Lts (508mm) 1.6 Lts
Temperature Ranges	4.4°C - 52°C (40°F - 125°F)

Large Diameter:

Available Lengths	250mm (9 ⁷ / ₈ " 508mm (20")
Outside Diameter	114mm (4 ¹ / ₂ "
Inside Diameter	25mm (1")
Canister Capacity	(250mm) 0.8 Lts (508mm) 1.6 Lts
Temperature Ranges	4.4°C - 52°C (40°F - 125°F)

Note:

- Capacities and Flow Rates are dependent on the types of Media used.
- The Cartridge Canister is supplied empty

Warning:

For drinking water applications, do not use water that is microbiologically unsafe or of unknown quality without adequate disinfection.

MODEL NUMBER

	10"	20"
Standard Diameter	WCECC10S	WCECC20S
Large Diameter	WCECC10L	WCECC20L