Carbon Cartridge - Large Diameter

The GAC series cartridges are designed for effective reduction of unwanted Chlorine Taste and Odour and also Organic Colour, Taste and Odour. They are designed to allow maximum contact between the water and the carbon ensuring maximum adsorption.

GGAnular Activated Carbon The construction of the cartridge allows water to enter through a pre-filter pad at the bottom and pass through the entire length of the carbon bed before exiting the cartridge at the other end. Before exiting, the water passes through a post filter to reduce any carbon fines and other sediment particles from the filtered water. The filter fits most standard Large Diameter 10" and 20" housings.

Typical Applications

- Price Competitive
- Granular Activated Carbon
- Designed for Maximum Adsorption

Features and Benefits

- Post-filter to Reduce Carbon Fines
- Individually Wrapped and Sealed
- Domestic
- Rural
- Potable water
- Commercial

General Specifications

Micron Ratings (Nominal): 10

250mm (9\%") Lengths:

508mm (20")

Outside Diameter: 114mm $(4\frac{1}{2})$

Inside Diameter: 28mm (11/8")

4.4°C - 52°C Temperature Ranges:

(40°F - 125°F)

Filter Capacity:

(per 250mm length) @ 3.8 lpm 45,600 Lts


(Estimated capacity based on 2.0 mg/l free available chlorine, capacity will vary depending on raw water quality.)

NOTE:

Recommended cartridge change is 6-9 months from date of installation, or earlier if required or at a maximum increased pressure differential of 69kPa (10psi), whichever occurs first.

Flow Performance

*Based on 10" length filter in clean water



Warning:

For drinking water applications, do not use water that is microbiologically unsafe or of unknown quality without adequate disinfection.



Model No.

10" 20"

WCGAC10L10 WCGAC20L10



arbon