

# AUTOTROL 368 CONTROL VALVE



## FEATURES/BENEFITS

Time-tested Duraflow flapper provides frictionless sealing for longer service life

Fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant

Optical sensor for precision cycle positioning

Designed with double backwash for reduced hardness leakage

Continuous service flow rate of 16.6 GPM with a backwash of 2.75 GPM

Backwash capability accommodates softener tanks up to 10"

Super capacitor for keeping time of day during power outage

Programming stored in memory and will not be lost due to power outages

History data for valve performance

Designed for single tank systems only

External drain line flow control

Softener only control valve

## OPTIONS

Plumbing connections in .75"-1.25" NPT, BSP, and sweat

Internal Autotrol\* turbine

**604-** Simple economic electronic time clock control.

**606-** Simple economic electronic meter control.



TESTED and CERTIFIED by the WQA to NFS/ANSI Standard 44 for Water Softener Performance.



UL recognized to the 979



TESTED EMC and Low Voltage Directive



Restriction of Hazardous Substance Compliant

## VALVE SPECIFICATIONS

Valve Body	Glass-filled Noryl
Rubber Components	Compounded for cold water
Operating Pressure	20-125 PSI (1.38-8.61 bar)
Water Temperature	35-100°F (2-38°C)
Ambient Temperature	35-122°F (2-50°C)
Refill Flow Rate	0.14 gpm (0.53 Lpm)/ 0.33 gpm (1.25 Lpm)

## ELECTRICAL

Controller	
Operating Voltage	12 volt– AC
Input Supply Frequency	50 or 60 Hz
Moter Input Voltage	12 volt– AC
Controller System	
Power Consumption	3 watts average

## TRANSFORMER- ALL CONTROLLERS

Transformer	
Output Voltage	12 volt– AC 400mA
Transformer	
Input Options	115 volt– AC 50/60 Hz 230 volt– AC 50/60 Hz 100 volt– AC 50/60 Hz
Transformer	
Plug Options	Indoor North American Plug Outdoor North American Plug Japanese Plug Taiwan/Korea Plug Australian Plug United Kingdown Plug Mainland Europe Plug

## VALVE CONNECTIONS

Tank Thread	2-1/2" – 8, male
Inlet/Outlet	3/4" BSPT, male 3/4" NPT, male 1 " BSPT, male 1" NPT, male
Drain Line	1/2" – BSPT, male 1/2" – NPT, male
Brine Line	3/8" – BSPT, male 3/8" – NPT, male

## DIMENSIONS

Riser Tube Dia.	1.05" (27 mm)
Riser Height	Flush to top of tank +/- 0.5"

## FLOW RATE

Service	
5 psi (1.03 bar) drop	16.6 gpm (4.3Cv) 3.77 m <sup>3</sup> /h (3.68kV)
Backwash	
25psi (1.72 Bar) drop	2.75 gpm (0.55Cv) 0.62 m <sup>3</sup> /h (0.48kV)
Service	
Backwash	3.68 Kv 0.48 Kv



13845 BISHOPS DR., SUITE 200, BROOKFIELD, WI 53005 USA  
P: 262.238.4400 | WATERPURIFICATION.PENTAIR.COM | CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com  
© 2018 Pentair Residential Filtration, LLC. All rights reserved.

§For a detailed list of where Pentair trademarks are registered, please visit [waterpurification.pentair.com/brands](http://waterpurification.pentair.com/brands). Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.

4002013 REV E JL18