

FILTER HOUSING

STANDARD DIAMETER

TYPICAL APPLICATIONS

- Whole House (20" Housing)
- Rural
- Point of Use (POU)
- Ice Machines
- Beverage Dispenser
- Recreation Vehicles
- Marine
- Domestic
- Commercial
- Light Industrial

The Blue Standard Diameter Filter Housing is manufactured from Polypropylene which has excellent chemical resistance enabling it to be used in a variety of applications within the Domestic, Rural, Commercial and Light Industrial fields. The Filter Housing has a Double O-Ring Seal built into the Housing Bowl providing it with added protection against leakage.

The Housing Cap has a Pressure Relief Button built in and mounting bosses to accommodate a Wall Mounting Bracket for easy installation. Unlike clear housings the Blue Polypropylene is opaque preventing light from penetrating which causes microbiological growth inside the filter housing.



GENERAL SPECIFICATIONS

Dimensions	10"	20"
Width	130mm (5.1")	130mm (5.1")
Height	335mm (13.2")	580mm (22.8")
Port Size	3/4" BSP	
Temperature Ranges	4.4°C - 43°C (40°F - 110°F)	
Operating Pressure (Maximum)	690 kPa (100 psi)	
Recommended Flow Rate (Maximum)	38 Lpm	76 Lpm

NOTE:

Flow rate will vary depending on the type of filter cartridge installed (Filter Cartridge is NOT included)

OPTIONAL EXTRAS :

	Part Number
Wrench	WAW1020HS
Single Mounting Bracket	WABS1020SW
Double Mounting Bracket	WABD1020SW34

Warning:

For drinking water applications, do not use water that is microbiologically unsafe or of unknown quality without adequate disinfection.

MODEL NUMBER

10 " Housing	20" Housing
WH10SB34DO	WH20SB34DO

HOUSING KITS WITH SINGLE BRACKET AND WRENCH

10 " Housing	20" Housing
WH10SB34DOK	WH20SB34DOK