AQUACORP

FILTER SYSTEM SINGLE UNDERSINK

FEATURES AND BENEFITS

- Reduced Chlorine Taste and Odour
- Reduces certain V.O.Cs and Pesticides
- Sparkling Clean, Fresh Tasting Water
- Continuous Supply of Filtered Water at your Finger Tips
- High Quality Water at a very Low Cost
- No More Bulky Water Dispensers or Storage Bottles
- Superior Quality Filter Cartridge
- Full Flavour from Tea, Coffee, Beverages and Cooking
- Simple Installation and Easy To Use

The Single Undersink filter system is designed for improving the quality and taste of Potable Water. The system uses a high quality carbon cartridge which will filter dirt particles like sand, silt and rust while reducing chlorine taste, odour and organics.

The cartridge supplied in our system will also remove 99.95% of Giardia and Cryptosporidium Cysts. The Single Undersink filter system accepts most standard 10" cartridges which enables a choice of Carbon Cartridge for different levels of filtration quality to suit your specific requirements.



*Cartridge supplied but not shown



AQUACORP

GENERAL SPECIFICATIONS

Connection	½" BSP (Female)		
Dimensions:	Height: 355mm (14")	Width: 145mm (5¾")	Depth: 145mm (5¾")
Temperature Ranges	4.4°C - 37.8°C (40°F - 100°F)		
Flow Rate (Maximum)	3.8 LPM (For best results run the system at 1 - 2 Lpm)		
Operating Pressure	690 kPa (100 psi) (Max.)		
Filter Capacity	@ 3.8 Lpm 189,300 Lts		

(Estimated capacity based on 2.0 mg/l free available chlorine, capacity will vary depending on raw water quality.)

NOTE:

Recommended cartridge change is 6-9 months from date of installation, or earlier if required or at a maximum increased pressure differential of 69 kPa (10psi), whichever occurs first.

Warning:

For drinking water applications, do not use water that is microbiologically unsafe or of unknown quality without adequate disinfection.

MODEL NUMBER	WSUFS
REPLACEMENT CARTRIDGE	WCCBC10S0.5

