

FILTER SYSTEM DUAL UNDERSINK

FEATURES AND BENEFITS

- Reduce Chlorine Taste and Odour
- Sparkling Clean Water
- Continuous supply of Filtered Water at your finger tips
- High Quality water at a very Low Cost
- Superior Quality Filter Cartridge
- No more Bulky Water Dispenser or Storage Bottles
- Simple Installation and easy to use
- Full Flavour from Tea, Coffee, Beverages and Cooking

The Dual Undersink filter system is designed for improving the quality and taste of Potable water. The system uses Two (2) filtration stages, the first stage is a Sediment Cartridge which is used to filter dirt particles like sand, silt and rust. The second stage is a Carbon Cartridge which is used to reduce chlorine taste, odour and also organics.

The cartridge supplied in our system will also filter 99.95% of Giardia and Cryptosporidium Cysts. The Dual Undersink filter system accepts most standard 10" cartridges which enables a wide range of filter cartridge combinations for different levels of filtration quality to suit your specific requirements.



*Cartridge supplied but not shown

GENERAL SPECIFICATIONS

Connection	½" BSP (Female)		
Dimensions:	Height: 350mm (13¾")	Width: 255mm (10")	Depth: 150mm (6")
Temperature Ranges	4.4°C - 37.8°C (40°F - 100°F)		
Flow Rate (Maximum)	3.8 LPM (For best results run the system at 1 - 2 Lpm)		
Operating Pressure	690 kPa (100 psi) (Max.)		
Filter Capacity	@ 3.8 Lpm 189,300 Lts		

(Estimated capacity based on 2.0 mg/l free available chlorine, capacity will vary depending on raw water quality.)

NOTE:

Recommended cartridge change is 6-9 months from date of installation, or earlier if required or at a maximum increased pressure differential of 69 kPa (10psi), whichever occurs first.

Warning:

For drinking water applications, do not use water that is microbiologically unsafe or of unknown quality without adequate disinfection.

MODEL NUMBER	W2SUFS
REPLACEMENT CARTRIDGE (STAGE 1, SEDIMENT)	WCMBL10S05
REPLACEMENT CARTRIDGE (STAGE 2, CARBON)	WCCBC10S0.5